

# DIRT LATE MODELS

## 4 BAR SUSPENSION CHASSIS

### Adjustment Recommendation Sheet

## Dry Slick Tracks Conditions

### LEFT FRONT

### RIGHT FRONT

E/C 4077-4/6-4 (DOUBLE ADJUSTABLE SHOCKS) E/C41715-10/6-4

30 psi.

(Gas Pressure)

30 psi.

Rebound position #4  
Reb. Pos. #6 for extreme slick tracks  
Comp. 8 clicks off full stiff

Rebound position # 9  
Comp. 4 clicks off full stiff

E4077-3/3

Fifth Coil Position #8

50 psi. gas pressure

### LEFT REAR

E42100/8-5

Shock in front of L.R.

75 psi.

(Gas Pressure)

Compression Adjustable  
at the eye of the shock  
Compression position #8

### LEFT REAR

### RIGHT REAR

E/C 4094-0.5/6-4 (DOUBLE ADJUSTABLE SHOCKS) E/C4096-4/5-2  
Shocks behind rear axle

30 psi.

(Gas Pressure)

30 psi.

Rebound position #1  
Comp. 8 clicks off full stiff

Rebound position # 1  
Comp. 4 clicks off full stiff  
Comp. 8 clicks off full stiff  
(Extreme Slick Conditions)



1698 Midwest Blvd. Indianapolis, IN 46214  
317.271.7100 | [www.advancedracing.net](http://www.advancedracing.net)