

Micro-Sprints on Dirt

3200 series Small Body Gas Shock

DRY / SLICK TRACKS

LEFT FRONT
3260.5/2 Valving
E3365-0.5/2
B3365-0.5/2
20 psi.

(Non-Adjustable Fronts)
(E-Model Adjustable Fronts)
(Cockpit Adjustable Fronts)
(Recommended Pressures)

RIGHT FRONT
3260.5/2 Valving
E3365-0.5/2
B3365-0.5/2
20 psi.

LEFT REAR
B3368-4/2

(Rebound Adjustable)
(Compression Adjustable)

RIGHT REAR

B3366-4/4
B3265/5-1

(Adjust Rebound & Compression at the same time)
Double Adjustable (Adjust Rebound & Compression independently)
10 psi. (Recommended Pressures)

BRC3366-3

B/C3366-3/6-3
10 psi.

FAST to AVERAGE TRACKS

LEFT FRONT
3262/1 Valving
E3265-0.5/2
A3265-0.5/2
10 psi.

(Non-Adjustable Fronts)
(E-Model Adjustable Fronts)
(Cockpit Adjustable Fronts)
(Recommended Pressures)

RIGHT FRONT
3262 Valving
E3265-0.5/2
B3265-0.5/2
10 psi.

LEFT REAR
B3368-4/2

(Rebound Adjustable)
(Compression Adjustable)

RIGHT REAR

B3366-4/4
B3265/5-1

(Adjust Rebound & Compression at the same time)
Double Adjustable (Adjust Rebound & Compression independently)
10 psi. (Recommended Pressures)

BRC3366-3

B/C3366-3/6-3
25 psi.

(Rear shocks can be 6" or 7" stroke depending on chassis manufacture)



1698 Midwest Blvd. Indianapolis, IN 46214
317.271.7100 | www.advancedracing.net